

Duble solenoid valves.

They are duple solenoid valves with four-way and three-positions, manufactured in sizes 20, 30 and 50 and in several circuits; are used in pilot systems and compact applications settled in manifolds.

The solenoid ETD series utilize power coils and are suitable for working till 315 bar.

The duty current coils (12-24-27 Volt) can be directly fed; otherwise for alternate current coils (24-110-220 Volt 50/60 Hz) a connector with rectifier bridge is required, which can be supplied on request.

Main features	Type	Q max. (l/min.)	P max. (bar)	Technical schedule
<p>ETD../43.. series - four-way type centre closed.</p>	ETD 20/4306	15	315	09.130
	ETD 30/4306	30	315	09.140
	ETD 50/4306	60	315	09.150
	ETD 20/4309	15	315	09.130
	ETD 30/4309	30	315	09.140
	ETD 50/4309	60	315	09.150
<p>ETD../43.. series - four-way type centre open.</p>	ETD 20/4307	12	315	09.160
	ETD 30/4307	25	315	09.170
	ETD 50/4307	45	315	09.180
	ETD 20/4308	12	315	09.160
	ETD 30/4308	25	315	09.170
	ETD 50/4308	45	315	09.180

Special circuits supplied on request.

On Customers request and for large quantity, solenoid valves with not standard circuits can be supplied. The circuits under mentioned are models already manufactured.

